



Outdoor

I-DIAL 24 VAC OUTDOOR

Controller

DESCRIPTION

I-DIAL is a new and unique electronic controller 4-6-8 station outdoor for residential application. The I-dial family is available at the same price both 24 VAC or 9 VDC solenoid. It follows the Rain's controllers philosophy and it allows to easily set the programming in 3 steps: start time, duration, frequency.

TECHNICAL CHARACTERISTICS

- 4 – 6 – 8 stations models
- Outdoor Model with Internal Transformer
- Electrical Power Supply: 220 VAC 50Hz
- Electrical Outputs: 24 Volts AC, 1.0 AMP
- 4 independent programs
- 4 independent start times (1 per each program)
- Next start time visualization
- Run Times: 1 min. to 240 min per station
- Watering cycles: from 4 per day up to 1 per week
- Watering Schedule: 7 day calendar with individual day selection, or 1 to 19 day interval watering
- Water Budgeting Mode from 10% to 200%
- Master Valve/Pump 24 VAC outlet can be enabled or disabled by station.
- Power Failure: 2 x 1.5 volt AA alkaline battery permanently maintains programs. (not included)
- Rain Sensor Inlet, programmable per each station
- Freeze-program function (OFF)
- Wide backlit LCD display
- Low-battery function
- Pump Start Relay connection enabled
- Permanent Memory Saves programs during power outages



1. NEW PROGRAMING METHOD




3. COVER



2. BATTERY COMPARTMENT



4. 3" BACKLIT LCD SCREEN



3

PROGRAM WITH 3 SIMPLE STEPS.



Code	Models	Box Qt.y	Box - cm
200.4083410	I-DIAL 4 24 VOLT 4 ZONES OUTDOOR	4	36x33x32
200.4083610	I-DIAL 6 24 VOLT 6 ZONES OUTDOOR	4	36x33x32
200.4083810	I-DIAL 8 24 VOLT 8 ZONES OUTDOOR	4	36x33x32

